



BF2.3 BF5

Technical specification

BF2.3

BF5

**HONDA
MARINE**

Exclusive
features

- Lightest 2.2–3.3hp engine available
- Centrifugal clutch for 'twist & go power'
- 'Fit & carry' pontoon bag available
- Neutral point
- Window oil indicator
- Emergency stop switch
- Underwater exhaust
- Manual engine trim and tilt
- Carry handle for easy portability
- Side storage feet
- 2 spare sheer pins & split pins
- 86dB(A) maximum noise at full RPM
- Frugal fuel consumption at 1.2L/hr
- Electronic Programmed Ignition
- Oil pressure alert indicator lamp
- Emergency stop switch
- Underwater exhaust
- Manual engine trim and tilt
- Side storage feet

Transom Height	S: 418mm L: 571mm	S: 445mm L: 572mm
Engine Type	Forced air cooled, 4-stroke OHV single cylinder	Water cooled, 4-stroke OHV single cylinder
Displacement	57cm ³	127cm ³
Bore Stroke	45 x 36mm	60 x 45mm
Compression Ratio	8.0:1	8.7:1
Max. Output	2.3hp (1.7kw) @ 5000rpm	5hp (3.7kw) @ 4000rpm
Full Throttle RPM Range	5000 – 6000rpm	4000 – 5000rpm
Idle Speed	2000rpm ± 100rpm	1550rpm ± 100rpm
Carburettor	Single carburettor	Single carburettor
Fuel	Unleaded petrol	Unleaded petrol
Fuel Tank	Integral 1 litre	Supplied with a 12.5 litre fuel tank
Lubricating System	Forced splash	Pressure lubrication
Oil Capacity	0.25 litre	0.55 litre
Ignition System	Transistorized contactless	Electronic PGM-IG
Starter and Controls	Recoil Tiller handle Throttle control setting	Recoil Tiller handle Throttle control setting
Charging coil	–	SEB & LEB only – 3 amp
Gear Ratio	2.42:1	2.1:1
Gear Shift	F - N and 360° pivot	F - N - R
Dry Weight (with Propeller)	S: 12.7kg L: 13.3kg	S: 27.0kg L: 27.5kg
Standard Prop Size	7 ¹ / ₄ x 4 ³ / ₄ in. (polyethylene)	7 ⁷ / ₈ x 6 ² / ₃ in. (alloy)
Trim/Tilt	Manual	Manual

