



BF15 BF20

Technical specification

HONDA
MARINE
**Exclusive
features**

- Accelerates quicker than all 2 and 4-strokes in its class
- Smooth Electronic Programmed Ignition
- Fuel enrichment system for easy starting
- The only 20hp 4-stroke on the market
- Oil pressure alert indicator lamp
- Emergency stop switch
- Through prop boss exhaust
- Over rev limiter
- Low speed power tilt available
- Saildrive thrust propeller available
- Lightest 20hp available

BF15

BF20

Transom Height	S: 433mm L: 563mm	S: 433mm L: 563mm
Engine Type	Watercooled, 4-stroke OHC 2 cylinder	Watercooled, 4-stroke OHC 2 cylinder
Displacement	350cm ³	350cm ³
Bore Stroke	59 x 64mm	59 x 64mm
Compression Ratio	9.2:1	9.2:1
Max. Output	15hp (11kw) @ 5000rpm	20hp (14.7kw) @ 5500rpm
Full Throttle RPM Range	4500 – 5500rpm	5000 – 6000rpm
Idle Speed	–	–
Carburettor	Single Carburettor	Single Carburettor
Fuel	Unleaded	Unleaded
Fuel Tank	Supplied with a 12.5 litre fuel tank	Supplied with a 12.5 litre fuel tank
Lubricating System	Pressure lubrication	Pressure lubrication
Oil Capacity	1.3 litre	1.3 litre
Ignition System	Electronic PGM-IG	Electronic PGM-IG
Starter and controls	Recoil/Electric Tiller handle or Remote control	Recoil/Electric Tiller handle or Remote control
Alternator	12 amp	12 amp
Gear Ratio	2.08:1	2.08:1
Gear Shift	F - N - R	F - N - R
Dry Weight (with Propeller)	S: 46.5kg L: 49.5kg	S: 46.5kg L: 49.5kg
Standard Prop size	9 ¹ / ₄ x 10in. (4 blade)	9 ¹ / ₄ x 10in. (4 blade)
Trim/Tilt	Manual, power tilt available	Manual, power tilt available



Domestic Use

Professional Use

