



BF8 BF10

Technical specification

HONDA
MARINE
**Exclusive
features**

- Accelerates quicker than other 4-strokes (different propellers available to maximise acceleration or thrust)
- Smooth Electronic Programmed Ignition
- Fuel enrichment system for easy cold starting
- 5 Year Warranty
- Audible oil pressure alert and indicator lamp
- Emergency stop switch
- Through prop boss and underwater exhaust
- Over rev limiter
- Saildrive thrust propeller available

BF8

BF10

Transom Height	S: 433mm L: 563mm	S: 433mm L: 563mm
Engine Type	Watercooled, 4-stroke OHC 2 cylinder	Watercooled, 4-stroke OHC 2 cylinder
Displacement	222cm ³	222cm ³
Bore Stroke	58 x 42mm	58 x 42mm
Compression Ratio	9.0:1	9.0:1
Max. Output	8hp (5.9kw) @ 4500rpm	10hp (7.4kw) @ 5500rpm
Full Throttle RPM Range	4500 – 5500rpm	5000 – 6000rpm
Idle Speed	-	-
Carburettor	Single carburettor	Single carburettor
Fuel	Unleaded	Unleaded
Fuel Tank	Supplied with a 12.5 litre fuel tank	Supplied with a 12.5 litre fuel tank
Lubricating System	Pressure lubrication	Pressure lubrication
Oil Capacity	1.3 litre	1.3 litre
Ignition System	Electronic PGM-IG	Electronic PGM-IG
Starter and controls	Recoil/Electric Tiller handle	Recoil/Electric Tiller handle or Remote control
Alternator	12 amp	12 amp
Gear Ratio	2.33:1	2.33:1
Gear Shift	F - N - R	F - N - R
Dry Weight (with Propeller)	S: 42kg L: 44.5kg	S: 42kg L: 44.5kg
Standard Prop size	9¼ x 9in. (4 blade)	9¼ x 9in. (4 blade)
Trim/Tilt	Manual	Manual



Domestic Use



Professional Use

